



金卤埋地灯 (HID)

除了兼顾星宝 I 各项优点外, 灯体高度减少是星宝 II 一大特点, 灯体高度 155mm, 含预埋件高度仅 200mm, 更适合在受深度限制的地方安装。适用于建筑装饰照明。

Opal plastic lens underneath tempered glass for diffusing light.
Integral control gear.
Input voltage: 175-265V AC.
LED brand: Cree, Lumileds or Osram.
Protection class: IP67.

Applications:
Decorative lighting for squares, parks, corridors etc.



防护等级 IP Rating IP 67
输入电压 Input Voltage AC220
显色性 Color rendering Ra>80
光源品牌 Lamp Brand OSRAM/PHILIPS/GE
环境温度 Operating Temperature -20°C~+50°C
面板材料 Cover 不锈钢 (Stainless steel)
灯体材质 Housing material 压铸铝 (Die cast aluminum)
灯体颜色 Finish color 皱纹黑(Wrinkles black)

不锈钢面环金卤光源系列(Stainless Steel Trim)



0308003.000	35W	CDM-T	G12	6°	0.5A	≤80°C
0308009.000	70W	CDM-T	G12	6°	0.98A	>80°C
0308004.000	35W	CDM-T	G12	12°	0.5A	≤80°C
0308010.000	70W	CDM-T	G12	12°	0.98A	>80°C
0308001.000	70W	CDM-TD	Rx7s	对称光	0.98A	>80°C

0308002.000	70W	CDM-TD	Rx7s	非对称光	0.98A	>80°C
-------------	-----	--------	------	------	-------	-------

压铸铝面环金卤光源系列(Die cast aluminum trim)

0308006.000	35W	CDM-T	G12	6°	0.5A	≤80°C
0307012.000	70W	CDM-T	G12	6°	0.98A	>80°C
0307007.000	35W	CDM-T	G12	12°	0.5A	≤80°C
0307013.000	70W	CDM-T	G12	12°	0.98A	>80°C
0307023.000	70W	CDM-TD	Rx7s	对称光	0.98A	>80°C


0307024.000	70W	CDM-TD	Rx7s	非对称光	0.98A	>80°C
-------------	-----	--------	------	------	-------	-------



配件 ACCESSORIES



200-0900040
磨砂玻璃
Frosted glass lens



8501060.000
宽光透镜 (宽光束)
Woven lens(wide beam)



8501061.000
椭圆扩展透镜 (可拉长光斑)
Elliptical spread lens